

APPLE SINGLE PHASE HYBRID INVERTER

SE 3.6KHB-60 SE 4.6/5/6KHB-120



HIGH YIELD

Max Efficiency: 97.3%
 Battery Efficiency: 94.3%
 Max Charge/Discharge Current: 120A
 Reasonable Energy Control: Increasing the proportion of spontaneous use.

HIGH RELIABILITY

BMS System: Ensuring high battery life
 Natural Cooling Design: Utilizing natural cooling mechanisms for efficient heat dissipation.

INTELLIGENT MAINTENANCE

Compatibility: Compatible with both lead-acid batteries and lithium battery energy storage systems
 Remote Configuration: Allows for remote setup and customization
 Remote Upgrade: Capability for remote software/firmware updates to enhance functionality.

Model	SE 3K6HB-60	SE4K6HB-120	SE5KHB-120	SE6KHB-120
Efficiency				
Max. efficiency (PV to AC)				97.3%
Max. efficiency (BAT to AC)				94.3%
Input (PV)				
MAX PV Power	6300W			9000W
Max PV voltage				550V
Max input current (input A/input B)				15A/15A
Max short current (input A/input B)				20A/20A
Start operating voltage				90V
MPPT voltage range				70V-540V
No. of MPPT trackers				2
String per MPP tracker				1
Input (BAT)				
Compatible battery type	Lithium-ion / Lead-acid			
Nominal battery voltage	48V			
Battery voltage range	40V-65V			
Max. charge/discharge current	60A/60A	120A/120A	120A/120A	120A/120A
Max. charge/discharge power	3000W/3000W	6000W/6000W	6000W/6000W	6000W/6000W
Lithium battery charge curve	Self-adaption to BMS			
Output (Grid)				
Nominal AC output power	3600W	4600W	5000W	6000W
Max. AC output apparent power	3600VA	4600VA	5500VA	6000VA
Max. AC output power (PF=1)	3600W	4600W	5500W	6000W
Max. AC output current	16A	22A	25A	27.2A
Rated AC voltage	230V L+N+PE			
AC voltage range	150V-300V (Adjustable)			
Rated grid frequency	50Hz/ 60Hz			
AC frequency range	45Hz-55Hz/55Hz-65Hz (Adjustable)			
Grid connection	Single phase			
Power factor	> 0.99 @rated power (Adjustable 0.8 LD - 0.8 LG)			
THDI	<3% (Rated Power)			
Output (Back up)				
Nominal output power	3000W	4600W	5000W	6000W
Nominal output current	13A	20A	21.7A	26A
Maximum power(Is)	6000VA	9200VA	10000VA	12000VA
Nominal output voltage	230V, L+N+PE			
Nominal output frequency	50Hz / 60Hz			
Transfer time	10ms (typ) / 20ms (max)			
THDV	<3% @100% R Load			
Protection				
Protection category	Class I			
DC switch	Support			
Anti-islanding protection	Support			
AC overcurrent protection	Support			
AC short circuit protection	Support			
DC reverse connection	Support			
Surge Arrester	DC Type III, AC Type III			
Insulation detection	Support			
Leakage current protection	Support			
PV overvoltage category	II			
AC overvoltage category	III			
Gen	Optional			
General				
Max. operation altitude	4000m			
Noise emission	<35dB			
Ingress protection degree	IP65			
Operating temperature range	-25 ~60			
Relative humidity	0~100%			
Cooling concept	Natural Cooling			
Mounting	Wall bracket			
Advanced parallel	Up to 9Pcs			
Dimensions (W*H*D)	515mm*485mm*175mm			
Weight	20Kg			25Kg
PV connection way	MC4/H4			
Battery connection way	Dedicated DC connector			
AC connection way (grid & back up)	Dedicated AC connector			
HMI & COM				
Display	LED+APP			
Communication interface	RS485/CAN (for BMS), RS485, USB, DRM/RS485 (for Meter), CAN			
Certification				
Grid	VDE-AR-N4105, IEC 61727/62116, AS 4777.2, EN 50549-1, IEC 62110, G21, NRS 097-2-1, RD 1699/661/413			
Safety	IEC62109-1&2, IEC62477-1			
Warranty	5 Years /10 Years (Optional)			

Remarks The range of output voltage and frequency may vary depending on the grid conditions.
 • Specifications are subject to change without advance notice.