

ET Series

40/50kW | Three Phase | 3/4 MPPTs
Hybrid Inverter (HV)

GoodWe's ET Series inverters, available in 40kW and 50kW capacities, are designed for commercial and industrial PV installations. These adaptable inverters seamlessly integrate into both on-grid and off-grid applications, facilitating parallel connections in either scenario. When paired with the Static Transfer Switch (STS) Box from GoodWe, the inverter not only ensures dependable UPS-level switching to backup mode but also interacts with diesel generators to efficiently replenish batteries. Moreover, the ET Series is compatible with diverse battery capacities and brands, including the GoodWe Lynx C, offering a comprehensive energy storage solution.



COMING
SOON



Smart Control & Monitoring

- <10ms UPS-level switching
- 110% unbalanced output



Friendly & Thoughtful Design

- Elegant and compact design
- Plug & Play installations



Superb Safety & Reliability

- Optional Type I+II SPD on DC side¹
- IP66 protection for outdoor installation safety
- AFCI optional¹



Flexible & Adaptable Applications

- Compatible with 182/210mm modules
- Up to 150% DC input oversizing
- 4 MPPTs, Max. efficiency up to 98.1%

Technical Data		GW40K-ET-10	GW50K-ET-10
Battery Input Data			
Battery Type		Li-Ion	
Nominal Battery Voltage (V)		500	
Battery Voltage Range (V)		200 ~ 800	
Start-up Voltage (V)		200	
Number of Battery Input		1	
Max. Continuous Charging Current (A)		100	
Max. Continuous Discharging Current (A)		100	
Max. Charging Power (W)	44000		55000
Max. Discharging Power (W)	44000		55000
PV String Input Data			
Max. Input Power (W)	60000		75000
Max. Input Voltage (V)		1000	
MPPT Operating Voltage Range (V)		165 ~ 850	
Start-up Voltage (V)		160	
Nominal Input Voltage (V)		620	
Max. Input Current per MPPT (A)	42 / 32 / 42		42 / 32 / 42 / 32
Max. Short Circuit Current per MPPT (A)	55 / 42 / 55		55 / 42 / 55 / 42
Number of MPP Trackers	3		4
Number of Strings per MPPT		2	
AC Output Data (On-grid)			
Nominal Output Power (W)	40000		50000
Nominal Apparent Power Output to Utility Grid (VA)	40000		50000
Max. Apparent Power Output to Utility Grid (VA)	44000		55000
Max. Apparent Power from Utility Grid (VA)	44000		55000
Nominal Output Voltage (V)		380 / 400, 3L / N / PE	
Output Voltage Range (V)		176 ~ 276	
Nominal AC Grid Frequency (Hz)		50 / 60	
AC Grid Frequency Range (Hz)		45 ~ 65	
Max. AC Current Output to Utility Grid (A)	60.6		75.8
Max. AC Current From Utility Grid (A)	60.6		75.8
Power Factor	~ 1 (Adjustable from 0.8 leading to 0.8 lagging)		
Max. Total Harmonic Distortion		<3%	
AC Output Data (Back-up)**			
Back-up Nominal Apparent Power (VA)	40000		50000
Max. Output Apparent Power (VA)	44000 (48000 at 60sec, 60000 at 10sec)		55000 (60000 at 60sec, 75000 at 10sec)
Max. Output Current (A)	66.7		83.3
Nominal Output Voltage (V)		380 / 400, 3L / N / PE	
Nominal Output Frequency (Hz)		50 / 60	
Output THDv (@Linear Load)		< 3%	
Efficiency			
Max. Efficiency		98.1%	
European Efficiency		97.5%	
Max. Battery to AC Efficiency		97.7%	
MPPT Efficiency		99.0%	
Protection			
PV String Current Monitoring		Integrated	
PV Insulation Resistance Detection		Integrated	
Residual Current Monitoring		Integrated	
PV Reverse Polarity Protection		Integrated	
Battery Reverse Polarity Protection		Integrated	
Anti-islanding Protection		Integrated	
AC Overcurrent Protection		Integrated	
AC Short Circuit Protection		Integrated	
AC Overvoltage Protection		Integrated	
DC Switch		Integrated	
DC Surge Protection		Type II (Type I + II Optional)	
AC Surge Protection		Type II	
AFCI		Optional	
Rapid Shutdown		Optional	
Remote Shutdown		Integrated	
General Data			
Operating Temperature Range (°C)		-35 ~ +60	
Relative Humidity		0 ~ 95%	
Max. Operating Altitude (m)		4000	
Cooling Method		Smart Fan Cooling	
User Interface		LED, WLAN + APP	
Communication with BMS		CAN	
Communication with Meter		RS485	
Communication with Portal		WIFI + LAN / 4G (Optional)	
Weight (kg)	62		65
Dimension (W × H × D mm)		520 × 660 × 260	
Topology		Non-isolated	
Self-consumption at Night (W)		< 15	
Ingress Protection Rating		IP66	
Mounting Method		Wall Mounted	

*1. Backup function can be only realized with STS Box (Static Transfer Switch Box).

*: Please visit GoodWe website for the latest certificates.

*: As a part of our policy of continuous improvement, we reserve the right to alter design and specifications without further notice.